

Technical Parameters

| | OA36-1 | OA36-2 | OL36-1 | OL36-2 | OL72-1 | OL72-2 |
|------------------------------|--|--|--|--|--|--|
| Max. speed | 18KM/H | 18KM/H | 18KM/H | 18KM/H | 18KM/H | 18KM/H |
| Max. mileage | 30KM | 40KM | 30KM | 40KM | 30KM | 40KM |
| Maximum bearing weight | 125KG | 150KG | 120KG | 150KG | 120KG | 150KG |
| Climbing capability | 30° | 45° | 30° | 45° | 45° | 45° |
| Turning radius | 0 | 0 | 0 | 0 | 0 | 0 |
| Cruise duration | 10 hours | 10 hours | 10 hours | 10 hours | 10 hours | 10 hours |
| Power | Two imported DC Motor, DC servo drives | DC brush motor | DC brush motor | DC brush motor | DC brush motor | DC brush motor |
| Motor power | 1000 watts ×2motors | 2×1000W | 2×1000W | 2×1000W | 2×1000W | 2×1000W |
| Battery type | PB,36V,42Ah | 36V, Lead-acid battery | 72V, High capacity Li-battery | 36V, High capacity Li-battery | 72V, High capacity Li-battery | 72V, High capacity Li-battery |
| Charging time | 8-10h | 6-8h | 6-10h | 3-5h | 6-10h | 3-5h |
| LCD display content | Battery capacity | Battery capacity, speed, miles | Battery capacity | Battery capacity, speed, miles | Battery capacity, speed, miles | Battery capacity, speed, miles |
| Pedal height | 26cm | 26cm | 26cm | 26cm | 26cm | 26cm |
| Max. height above the ground | 13cm | 13cm | 13cm | 13cm | 13cm | 13cm |
| Standard pressure of tyre | 100kpa | 250kpa | 250kpa | 250kpa | 250kpa | 250kpa |
| Handlebar height | 80-110cm Adjustable | 80-110cm Adjustable | 80-110cm Adjustable | 80-110cm Adjustable | 80-110cm Adjustable | 80-110cm Adjustable |
| Tyre size | 19 in / 48 cm vacuum smooth (puncture proof) | 19 in / 48 cm vacuum smooth (puncture proof) | 19 in / 48 cm vacuum smooth (puncture proof) | 19 in / 48 cm vacuum smooth (puncture proof) | 19 in / 48 cm vacuum smooth (puncture proof) | 19 in / 48 cm vacuum smooth (puncture proof) |
| Packaging size | 90×52×63cm | 85cm×49cm×65cm | 85cm×49cm×65cm | 85cm×49cm×65cm | 85cm×49cm×65cm | 85cm×49cm×65cm |